



LÁMPARAS HALÓGENAS DE BAJO VOLTAJE




MR16

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | BASE | TEM. COLOR (K) | VIDA HRS. |
|------------|----------|------------------|--------------|-------|----------------|-----------|
| 17-101-29X | F-9049-0 | MR16 38° 12V S/C | 20 | GX5.3 | 3000 | 3000 |
| 17-102-29X | F-9105-0 | MR16 38° 12V S/C | 35 | GX5.3 | 3000 | 3000 |
| 17-103-29X | F-9047-0 | MR16 38° 12V S/C | 50 | GX5.3 | 3000 | 3000 |
| 17-104-29X | F-9119-0 | MR16 38° 12V S/C | 50 | GX5.3 | 3000 | 1000 |




MR11

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | BASE | TEM. COLOR (K) | VIDA HRS. |
|------------|----------|------------------|--------------|------|----------------|-----------|
| 17-201-29X | F-9046-0 | MR11 38° 12V S/C | 35 | G4 | 3000 | 3000 |




JCT3

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | BASE | TEM. COLOR (K) | VIDA HRS. |
|------------|----------|-------------|--------------|------|----------------|-----------|
| 17-301-29X | F-9126-0 | JCT312V | 20 | G4 | 3000 | 2000 |




AR111

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | ★° | BASE | TEM. COLOR (K) | VIDA HRS. |
|------------|----------|-------------|--------------|----|------|----------------|-----------|
| 17-601-39X | F-8010-0 | AR111 12V | 50 | 24 | G53 | 3000 | 3000 |
| 17-602-39X | F-8010-1 | AR111 12V | 50 | 8 | G53 | 3000 | 3000 |




LÁMPARAS HALÓGENAS PARA TENSIÓN DE LÍNEA




MR16

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | BASE | TEM. DE COLOR (K) | VIDA HRS. |
|------------|----------|--------------------------|--------------|-------|-------------------|-----------|
| 17-106-23X | F-9118-0 | MR16 38° 127V C/CUBIERTA | 50 | GX5.3 | 3000 | 2000 |



GU10

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | BASE | TEM. COLOR (K) | VIDA HRS. |
|------------|----------|--------------------------|--------------|------|----------------|-----------|
| 17-401-23X | F-9114-0 | GU10 40° 127V C/CUBIERTA | 50 | GU10 | 2700 | 1500 |



G9

| CLAVE A | CLAVE B | DESCRIPCIÓN | POTENCIA (W) | BASE | TEM. COLOR (K) | VIDA HRS. |
|------------|----------|-------------|--------------|------|----------------|-----------|
| 17-501-23X | F-9111-0 | G9 127V | 40 | G9 | 2700 | 1500 |

